


TOSHIBA


COLOUR TELEVISION


221F3W:261F3W



SPECIFICATIONS

INPUT POWER RATING:	103 watts (nominal), 220 volts AC, 50Hz	
AERIAL INPUT IMPEDANCES:	75 ohm unbalanced type VHF and UHF	
RECEIVING CHANNELS:	VHF channels channels E2 to E4, E5 to E12, and C	
	UHF channels channels E21 to E69	
INTERMEDIATE FREQUENCIES:	Picture I-F carrier frequency 38.9 MHz	
	Sound I-F carrier frequency 33.4 MHz	
	Color sub-carrier frequency 34.47 MHz	
CHASSIS CONSTRUCTION:	IC-Solid State, Horizontal Chassis	
PICTURE TUBE:	22 in. A56-715X, 530 mm 26 in. A67-715X, 626 mm (measured on diagonal of viewable picture area) 110° Deflection	
SOUND OUTPUT:	3.5 watt (at 10% harmonic distortion)	
SPEAKER:	Oval, 105 × 156 mm, 15 ohms	
CABINET:	Table type	
DIMENSION:	22 in.	26 in.
	Height 475 mm	539 mm
	Width 688 mm	774 mm
	Depth 420 mm	459 mm
WEIGHT (NET):	22 in.: 25.5 kg, 26 in.: 33.4 kg	





U902 MAIN BOARD PW3691


U602 HEADPHONE/RECORDING BOARD PW3060

CHROMINANCE SIGNAL


U901 CRT DRIVE BOARD PW3598

SECAM CHROMA MODULE (SERVICE ATTACHMENT NOT BUILT IN)

U301 DPC PW3491A



U902 MAIN BOARD PW3691 (Foil Side)



UA01A RMT/SELECTOR BOARD PW3694-1 (Foil Side)

